



VIEW W/O SUPPORTS

NOTE: 1) SHIP LOOSE W/ (2) 1 1/2" x 48" LG. FLEX. MAG. ANODES.
 2) HYDRO @ 240 PSIG. MIN.
 3) SHELL: 4-22-04 PROOF TEST.

| | | | |
|------------------------------|--|---|----------------|
| SHELL / HEADS | | .245" SA-455 2:1 S.E. | |
| JOGGLE | | | |
| M.A.W.P. | | 160 | PSIG. @ 210 °F |
| ASME SECTION IV | | 2013 | |
| X-RAY: | | RT-NO / H.L.W. | |
| GALLONS: | | 1080 | WT. 1608 LBS. |
| SERIAL NO. | | | |
| INSIDE: | | GLASS LINED | |
| OUTSIDE: | | PRIME | |
| CAD-"B" UNDER "STD"-SERIES | | | |
| BY: E.S. | | SCALE: 3/4"=12" | |
| ROY E. HANSON JR. MFG. | | 1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021 | |
| GS-48-1080-H | | REV. 1-16-14 | DATE: 5-21-90 |
| FOR: HANSON STANDARD | | | |
| HORIZ. HOT WATER TANK | | | |
| SURFACE AREA = 164.5 SQ. FT. | | | |