



OTHER	CALIF.	
79.8%	86 1/2%	LIQUID LEVEL
31 1/2"	17"	"A"
42.9"	28.4"	D.T. ON N.PL.

SHELL / HEADS	
M.A.W.P.	250 PSIG. @ 200 °F
M.D.M.T.	-20 °F @ 250 PSIG.
ASME SECTION VIII	DIV. 1, 2004 ADD 2005
X-RAY:	RT-4 SPOT L.S. & HDS. G.S.
GALLONS:	1150 WT. 2906 LBS.
SERIAL NO.	
N.B.	

NOTE: 1) HYDRO @ 327 PSIG. MIN.
2) INTERNAL PIPES PER: PA-412-B-1B

PA-412-B	REV. 4-24-06
FOR: HANSON STANDARD	DATE: 4-17-86
VERT. L.P.G. TANK	
SURFACE AREA = 194.1 SQ. FT.	
C.F.M. REQ'D 4033	
INSIDE: UNPAINTED & DEHYDRATE	
OUTSIDE: PRIME	
LEG ZONE: 4-15 KM.	
BY: E.S.	SCALE: 1/2" = 12"
ROY E. HANSON JR. MFG.	
1924 COMPTON AVE.	
LOS ANGELES, CA 90011	

