



NOTE: 1) HYDRO @ 195 PSIG. MIN.

SHELL / HEADS		.250" SA-455 2:1 S.E. (.212" MIN.)	
M.A.W.P.	150 PSIG. @ 400 °F		
M.D.M.T.	-20 °F @ 150 PSIG.		
ASME. SECTION VIII	DIV. 1, 2010 ADD 2010		
X-RAY: RT-4 SPOT L.S. & HDS. G.S.			
GALLONS: 2520	WT. 3474 LBS.		
SERIAL NO.			
N.B.			
INSIDE: UNPAINTED		60-VP-2520-R	
OUTSIDE: PRIME		REV. 8-10-11	
CAD "B" SIZE UNDER "STD"-SERIES		DATE: 3-5-99	
BY: J.G. SCALE: 1/2" = 12"		FOR: HANSON STANDARD	
INSIDE: UNPAINTED		VERT. AIR TANK	
OUTSIDE: PRIME		UW-21(b)	
CAD "B" SIZE UNDER "STD"-SERIES		INSIDE: UNPAINTED	
BY: J.G. SCALE: 1/2" = 12"		OUTSIDE: PRIME	
ROY E. HANSON JR. MFG.		1600 E. WASHINGTON BLVD.	
LOS ANGELES, CA 90021			